

Description

QUALI-FILTRES baskets are available as standard or can be designed and manufactured to meet your specific requirements. We are able to offer baskets that can be adapted to your existing installations and filters.

Features & Benefits

- Available in 316L
- Other materials (titanium, steel...) on request
- Wide chemical compatibility
- Filtration threshold: from 25µm to 3mm.
- Smooth or pleated basket for improved retention capacity.
- Araldite bonded or argon welded.



Application

Raw water
Oil
Kerosene
Adhesive
Varnish
Manometers
Cooling water Heating circuit
Washing water
Hydraulic oil
Paint

Deionised water
Polymers
Solvents
Resins
Fuels
Oil
Acid
Alcohol
Solvent
Gas
Lubricating oil

Maximum operating temperature

°C	Filter medium
400°C	Argon welded
70°C	Araldite bonded

Maximum differential pressure Δ

Δ p recommended for cleaning: 1.5 bar
 Δ p maximum: 5 bar

Order reference

QT reference

- **L** - **SA** - **300** - **250** - **146** - **V**
Tab 1 Tab 2 Tab 3 Tab 4 Tab 5 Tab 6

Table 1 : Media

Code	Description
L	Smooth
P	Pleated

Table 2 : Assembly

Code	Description
CA	Araldite bonded
SA	Argon welded

Table 3 : Retention threshold

Code	Description
25	25μ
50	50μ
100	100μ
300	300μ
500	500μ
750	750μ
1000	1000μ
2000	2000μ
3000	3000μ

Table 4 : Lenght

Code	Description
250	250 mm
400	400 mm
450	450 mm
500	500 mm
550	550 mm
600	600 mm
730	730 mm
750	750 mm
800	800 mm
810	810 mm
930	930 mm
1000	1000 mm

Table 5 : diameter

Code	Description
104	104 mm
125	125 mm
146	146 mm
170	170 mm
180	180 mm
200	200 mm
230	230 mm
250	250 mm
280	280 mm
315	315 mm
365	365 mm

Table 6 : Seal option

Code	Description
V	Viton
S	Silicone