



DESCRIPTION

Composed of 100% synthetic polyester fibers with thermal bonding.

Completely chemically inert.

High mechanical, chemical, and thermal resistance.

Excellent permeability, especially with high-viscosity neat oil.

ORDER REFERENCE

Example :

QBAND -PETF - A
50 - B
500 - C
100

A / Weight

Code	Weight	Thickness	Air Permeability	Nominal Filtration Threshold
25	25 gm/m ²	0,14 mm	2100 l/(m ² -s) @ 50 Pa	50 µm
32	32 gm/m ²	0,2 mm	1750 l/(m ² -s) @ 50 Pa	40 µm
50	50 gm/m ²	0,2 mm	2200 l/(m ² -s) @ 50 Pa	30 µm
70	70 gm/m ²	0,28 mm	2600 l/(m ² -s) @ 100 Pa	20 µm

B / Width of web

Code	Width
500	500 mm
700	700 mm
1000	1000 mm

Other widths available upon request

Material

Thermally bonded polyester

BAND FILTER COMPATIBILITY

✓ **GRAVITY FLAT**

✓ **HYDROSTATIC**

✓ **COMPACT DRUM**

✓ **PRESSURE BAND**
> 70g/m²

✓ **VACUUM BAND**
> 70g/m²

C / Length

Code	Length
100	100 m

Other lengths available upon request