

DESCRIPTION

Made from 100% polypropylene fibre. Thermal binder. It is characterised by the 'welding points' present on all the reels.



This range is very homogeneous and very thin, giving it a high level of nominal efficiency.

Oleophilic by nature, it is rarely used on whole oils. On the other hand, it will tend to remove foreign oils from emulsions.

Mechanically, chemically and thermally resistant, it can be used on any filtration system.

ORDER REFERENCE

Example :

QBAND -PPP - **A** 30 - **B** 500 - **C** 100

A / Weight

Code	Weight	Thickness	Air Permeability	Nominal Filtration Threshold
30	30 gm/m ²	0,34 mm	4200 l/(m ² ·s)	40 µm
50	50 gm/m ²	0,42 mm	2400 l/(m ² ·s)	30 µm
70	70 gm/m ²	0,47 mm	1500 l/(m ² ·s)	20 µm
100	100 gm/m ²	0,58 mm	900 l/(m ² ·s)	10 µm





B / Width of web

Code	Width
500	500 mm
700	700 mm
1000	1000 mm
1300	1300 mm
1500	1500 mm
1800	1800 mm
2300	2300 mm

Material

Polypropylene

BAND FILTER COMPATIBILITY



C / Length

Code	Length
100	100 m
250	250 m

Other lengths available upon request